

# MeshMax Product Series

## Convergence of WiMAX, Wi-Fi Mesh and WiFi

### Proxim's MeshMAX Supports WiMAX, Wi-Fi Mesh, and Wi-Fi

Proxim's MeshMAX product line integrates three technologies in one unit. The new MeshMAX product is a tri-radio, outdoor device offering Wi-Fi connectivity for access, Wi-Fi mesh gateway for network redundancy and a high capacity, carrier-class WiMAX link for backhaul. The convergence of these three technologies delivers end-to-end QoS for triple-play applications, a reduction in total cost of ownership and investment protection for future developments in WiMAX. The MeshMAX Series consists of two versions. MeshMAX Model 3500WM includes one radio for WiMAX backhaul, one radio for Wi-Fi Mesh and one radio for 802.11b/g Wi-Fi access. Expanding the Wi-Fi coverage, Model 3500W will use one radio for WiMAX backhaul and two radios for tri-mode Wi-Fi access, supporting 802.11a and 802.11b/g clients. The MeshMAX Series provides an optimal solution which brings internet connectivity and applications to where the customers are and where they want to be.

Drawing on Proxim's expertise in WiMAX and Wi-Fi Mesh Technologies, the MeshMAX product line encapsulates the best in class features of the award-winning Tsunami WiMAX and ORiNOCO mesh product families. Proxim is uniquely positioned to offer this leading-edge product given our extensive experience in delivering Wi-Fi and WiMAX solutions.

- End-to-end product portfolio consisting of WLAN, Wi-Fi Mesh, WiMAX and Point-to-Point
- Based on WiMAX Forum Certified Tsunami MP.16 and Wi-Fi certified ORiNOCO access points
- Tri-radio design provides one radio for WiMAX backhaul for distribution, one radio for Wi-Fi mesh link and one radio for exclusive Wi-Fi access traffic
- End-to-end QoS from access to distribution to support voice and video
  - IEEE 802.11e draft QoS support for access and enhanced QoS on mesh link
  - IEEE 802.16e QoS support for WiMAX wireless backhaul link
  - 802.1D to 802.1p priority mapping and 802.1D to IP DSCP mapping
- Low latency enables VoIP
- Enhanced security with AES encryption protects over the air transmission on all three links
- Scalable, flexible end to end Proxim solutions allow for ease in expansion of network
  - Service Provider can expand WiMAX network coverage with MeshMAX by extending their network utilizing Wi-Fi mesh
  - Enterprise WiMAX subscribers can extend internet access to local clients through Wi-Fi hotspot

### Simplifies Network Architecture, Deployment, And Management

Reducing network complexity, minimizing time of deployment and increasing ease of installation, the MeshMAX accelerates the network operator's time to money.

- Less nodes to install, deploy and manage
- Single management interface reduces time for service and support
- Centralized remote management support with ProximVision™ Network Management System
- Provides consistent deployment and user experience to Tsunami™ MP.11, Tsunami MP.16 and ORiNOCO Mesh Access Point product lines
- Reduces downtime and network troubleshooting compared to multi-vendor WiMAX and Wi-Fi Mesh network

## Product Overview



## Significantly Reduces Total Cost Of Ownership (TCO):

- Lowest deployment cost per square mile
- Reducing the number of nodes decreases installation and management time and minimizes associated costs
- Low power consumption and solar power options reduce operating expenses

## Product Overview

### Investment Protection:

WiMAX and mesh networks consisting of the Tsunami WiMAX products, ORiNOCO Mesh Access Points and MeshMAX (IEEE 802.16e) radios enable a service provider to establish a customer base and capture a head start on securing the WiMAX mobile market.

- Current MeshMAX product features WiMAX QoS and 802.16e class roaming with unprecedented mobility capabilities
- MeshMAX platform enables support of all mobile WiMAX and Wi-Fi clients

**LTI DataComm**  
 23020 Eaglewood Ct. #100  
 Sterling, VA 20166  
[www.ltidata.com](http://www.ltidata.com)  
 800-677-5050

RADIO & TRANSMISSION	
<b>Product Models</b>	9100-XX, MeshMAX 3500WM Tri-radio, WiMAX subscriber and Wi-Fi Mesh access point 9101-XX, MeshMAX 3500W Tri-radio, WiMAX subscriber and Wi-Fi access point
<b>Frequency Bands</b>	3.4 – 3.6 GHz for WiMAX 5.15 – 5.85 GHz and 2.412 – 2.472 for Mesh and Wi-Fi
<b>RF Modulation and Over the Air Data Rates</b>	OFDM (Orthogonal Frequency Division Multiplexing)
<b>BPSK</b>	3.5 GHz Band – 3.5 MHz, 7MHz, 1.4 Mbps, 2.8 Mbps 5 GHz Band – 6 and 9 Mbps 2.4 GHz Band – 6 and 9 Mbps
<b>QPSK</b>	3.5 GHz Band – 3.5 MHz, 7MHz, 2.8 and 4.2 Mbps, 6.6 and 8.5 Mbps 5 GHz Band – 12 and 18 Mbps 2.4 GHz Band – 12 and 18 Mbps
<b>16-QAM</b>	3.5 GHz Band – 3.5 MHz, 7MHz, 5.6 and 8.5 Mbps, 11.3 and 16.9 Mbps 5 GHz Band – 24 and 36 Mbps 2.4 GHz Band – 24 and 36 Mbps
<b>64-QAM</b>	3.5 GHz Band – 3.5 MHz, 7MHz, 11.3 and 12.7 Mbps, 22.6 and 25.4 Mbps 5 GHz Band – 48 and 54 Mbps 2.4 GHz Band – 48 and 54 Mbps
<b>DSSS (For 2.4 GHz Radio Only)</b>	DBPSK – 1 Mbps DQPSK – 2 Mbps CCK – 5.5 and 11 Mbps
<b>Channel Bandwidth</b>	3.5 MHz and 7 MHz for WiMAX radio, 20 MHz for mesh backhaul and Wi-Fi access
<b>Output Power</b>	3.5 GHz: +21dBm 5 GHz: +18dBm 2.4 GHz: +20dBm 14.57
<b>Wired Ethernet</b>	10/100 Base-T Ethernet (RJ-45)
<b>Antenna Connector</b>	Three Type-N Female connectors (one for 3.5 GHz, one for 5 GHz, and one for 2.4 GHz)
PHYSICAL & ENVIRONMENTAL	
<b>Dimensions</b>	Packaged – 20dBm 14.57 in x 13.70 in x 8.19 in (370 mm x 348 mm x 208 mm) Unpackaged - 10.5 in x 10.5 in x 3.25 in (267 mm x 267 mm x 83 mm)
<b>Weight</b>	Packaged – 12 lbs (5.44 kg) Unpackaged - 5.5 lbs (2.49 kg)
<b>Temperature</b>	Operating - 33° to 60°C Storage - 55° to 80°C
<b>Humidity</b>	CMax 100% relative humidity (non-condensing)
<b>Wind Loading</b>	125 mph
<b>Power Supply</b>	PoE: 110/240 VAC (input); 48 VDC 48V @ 420mA MAX (output)
<b>(OPT) Power Supply</b>	110/240 VAC light pole power tap (purchased separately)
<b>LEDS</b>	Two indicators on the RJ-45 connector to indicate power/Ethernet traffic and mesh traffic
MANAGEMENT & WARRANTY	
<b>Local</b>	RS-232 Serial Port; DB9 Female
<b>Remote</b>	WiMAX: Telnet/CLI, HTTP, TFTP; SNMP v1, v2 (MIBII, Proxim MIBs, Bridge MIB, RIPv2MPB, 802.16 MIB, Etherlike MIB) Mesh and Wi-Fi: SNMP v1; SNMP v2c and SNMP v3, ORINOCO, RFC1213; 802.11I-d3; IANAifType-MIB; MIB802, DHCP, Telnet, HTTP, TFTP, BootP
<b>MTBF and Warranty</b>	100,000 hours; 1 Year Parts and Labor (extended warranty and enhanced support available with purchase of ServPak)
PACKAGE CONTENTS	
<b>Package Contents</b>	<ul style="list-style-type: none"> <li>• One MeshMAX 3500WM Tri-radio, WiMAX subscriber and Wi-Fi Mesh access point <b>OR</b></li> <li>• One MeshMAX 3500W Tri-radio, WiMAX subscriber and Wi-Fi access point</li> <li>• One wall/pole mounting bracket</li> <li>• One Power over Ethernet injector and power cord</li> <li>• One Ethernet cable weather-proof plug</li> <li>• One Installation CD-ROM with Software and Documentation</li> </ul>