

Motorola PTP 58600 & 54600

5.8 and 5.4 GHz Point-to-Point Bridges

Spectrum-Efficient, High-Availability Wireless Ethernet Bridges

The Motorola wi4 Fixed Point-to-Point Wireless Ethernet Bridges – PTP 600 Series – bring together the speed and reliability of licensed wireless with the flexibility of the unlicensed space. Operating in the 5.4 and 5.8 GHz bands at Ethernet data rates up to 300 Mbps, the systems are designed for virtually any environment – non-line-of-sight, line-of-sight and high interference – where high throughput is a major requirement and/or single or dual T1/E1 capability is needed.

Through Motorola's unique combination of technologies, PTP 600 Series solutions enhance link performance in a variety of applications, including T1 replacement, Voice-over-IP, video surveillance, distance learning, telemedicine and high-speed backhaul.

The PTP 600 Series bridges are part of Motorola's MOTOwi4 portfolio of innovative wireless broadband solutions that create, complement and complete IP networks. Delivering IP coverage to virtually all spaces, the MOTOwi4 portfolio includes wi4 Fixed, wi4 Mesh, wi4 Indoor and wi4 WiMAX solutions for private and public networks.



Part Numbers:

Motorola PTP 58600:

- BP5830BH-2 Integrated
- BP5830BH15-2 Integrated Lite
- BP5830BHC-2 Connectorized
- BP5830BHC15-2 Connectorized Lite

Motorola PTP 54600:

- BP5530BH-2 Integrated
- BP5530BH15-2 Integrated Lite
- BP5530BHC-2 Connectorized
- BP5530BHC15-2 Connectorized Lite

Product Datasheet



RADIO TECHNOLOGY

RF Band	5.725 – 5.850 GHz, 5.470 – 5.725 GHz
Channel Size	30 MHz
Channel Selection/Dynamic Frequency Control	By <i>intelligent</i> Dynamic Frequency Selection (<i>i</i> -DFS) or manual intervention; automatic selection on start-up and continual adaptation to avoid interference; 10 MHz step size for WiMAX compatibility
Transmit Power	Varies with modulation mode and settings from -7 dBm to 25 dBm
System Gain	Integrated: Varies with modulation mode; up to 162 dB using 23 dBi integrated antenna Connectorized: Varies with modulation mode and antenna type
Receiver Sensitivity	Adaptive, varying between -91 dBm and -58 dBm
Modulation	Dynamic; adapting between BPSK and 64 QAM dual
Error Correction	FEC, ARQ
Duplex Scheme	TDD ratio: Dynamic or Fixed; same or split frequency Tx/Rx
Antenna: type/gain/B/W	Integrated: Integrated flat plate 23 dBi / 7° Connectorized: Approved to operate with flat plate up to 28 dBi or parabolic dish up to 37.7 dBi; connected via 2 x N-type female
Range	Up to 200 km (124 miles)
Security and Encryption	Proprietary scrambling mechanism; optional 128/256 Bit AES, FIPS 197

ETHERNET BRIDGING & E1/T1

Protocol	IEEE 802.3
User Data Throughput	Integrated and Connectorized: Dynamically variable up to 300 Mbps at the Ethernet (aggregate) Integrated and Connectorized: Dynamically variable up to 150 Mbps at the Ethernet (aggregate)
Latency (one way)	<1 ms each direction
Interface	10/100/1000 Base T (RJ-45) – auto MDI/MDIX, 1000 Base SX option
T1/E1 Interface	G703/G704, G823/G824 Integrated and Connectorized: Provides dual T1/E1 ports Integrated and Connectorized Lite: Provides a single T1/E1 port

MANAGEMENT & INSTALLATION

LED Indicators	Power status, Ethernet link status and activity
System Management	Web or SNMP using MIB-II, WiMAX and private MIB; Canopy® Prizm
Installation	Built-in audio assistance for link optimisation
Connection	Distance between outdoor unit and primary network connection: up to 100 metres (330')

PHYSICAL

Dimensions	Integrated Outdoor Unit (ODU): Width 370 mm (14.5"), Height 370 mm (14.5"), Depth 95 mm (3.75") Connectorized ODU: Width 309 mm (12.2"), Height 309 mm (12.2"), Depth 105 mm (4.1") Powered indoor unit (PIDU Plus): Width 250 mm (9.75"), Height 40 mm (1.5"), Depth 80 mm (3")
Weight	Integrated ODU: 5.5 kg (12.1 lbs) including bracket Connectorized ODU: 4.3 kg (9.1 lbs) including bracket PIDU Plus: 864 g (1.9 lbs)
Wind Speed	242 kph (150 mph)
Power Supply	Integrated with Indoor Unit
Power Source	90–240 VAC, 50–60 Hz / 36–60V DC; redundant powering configurations supported
Power Consumption	55 W max

ENVIRONMENTAL & REGULATORY

Operating Temperature	-40°C (-40°F) to +60°C (+140°F), including solar radiation
Protection and Safety	UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950
Radio	5.8 GHz: FCC Part 15, sub-part C 15.247, Eire ComReg 03/42, UK Approval to IR2007 5.4 GHz: EN 301 893
EMC	USA–FCC Part 15, Class B; Europe–EN 301 489-4

LTI DataComm
23020 Eaglewood Ct. #100
Sterling, VA 20166
www.ltidata.com
800-677-5050